

# NAHTLOSE STAHLROHRE

## Seamless steel tubes

### 25CrMo4

Zugfestigkeit 650 - 850 N/mm<sup>2</sup>  
Maßangabe: Außendurchmesser x Wandstärke

*Tensile strength 650 - 850 MPa  
Dimensions: OD x wall thickness*

10 x 1,0 mm	18 x 1,0 mm	22 x 2,0 mm	30 x 2,0 mm	40 x 1,0 mm
12 x 1,0 mm	18 x 1,5 mm	25 x 1,0 mm	30 x 2,5 mm	40 x 1,5 mm
12 x 2,0 mm	18 x 2,0 mm	25 x 1,5 mm	30 x 3,0 mm	40 x 2,0 mm
13 x 1,5 mm	20 x 0,5 mm	25 x 2,0 mm	32 x 1,0 mm	45 x 1,5 mm
14 x 1,0 mm	20 x 0,8 mm	25 x 2,5 mm	32 x 1,5 mm	45 x 2,0 mm
14 x 2,0 mm	20 x 1,0 mm	28 x 1,0 mm	32 x 2,0 mm	45 x 2,5 mm
16 x 1,0 mm	20 x 1,5 mm	28 x 1,5 mm	32 x 2,5 mm	50 x 2,0 mm
16 x 1,5 mm	20 x 2,0 mm	28 x 2,0 mm	35 x 1,0 mm	
16 x 2,0 mm	22 x 1,0 mm	30 x 1,0 mm	35 x 1,5 mm	
16 x 2,5 mm	22 x 1,5 mm	30 x 1,5 mm	35 x 2,0 mm	

### 15CDV6

Zugfestigkeit 980 - 1180 N/mm<sup>2</sup>  
Maßangabe: Außendurchmesser x Wandstärke

*Tensile strength 980 - 1180 MPa  
Dimensions: OD x wall thickness*

12 x 1,0 mm	18 x 1,0 mm	25 x 1,0 mm	30 x 2,0 mm	40 x 1,5 mm
12 x 1,5 mm	18 x 1,5 mm	25 x 1,5 mm	30 x 3,0 mm	40 x 2,0 mm
12 x 2,0 mm	18 x 2,0 mm	25 x 2,0 mm	32 x 1,0 mm	40 x 3,0 mm
14 x 1,0 mm	20 x 1,0 mm	25 x 2,5 mm	32 x 1,5 mm	45 x 1,5 mm
14 x 1,5 mm	20 x 1,5 mm	28 x 1,0 mm	32 x 2,0 mm	45 x 3,0 mm
14 x 2,0 mm	20 x 2,0 mm	28 x 1,5 mm	35 x 1,0 mm	50 x 1,5 mm
16 x 1,0 mm	22 x 1,0 mm	28 x 2,0 mm	35 x 1,5 mm	50 x 3,2 mm
16 x 1,5 mm	22 x 1,5 mm	30 x 1,0 mm	36 x 1,0 mm	55 x 1,5 mm
16 x 2,0 mm	22 x 2,0 mm	30 x 1,5 mm	40 x 1,0 mm	64 x 2,0 mm

Weitere Abmessungen sind auf Anfrage erhältlich – wir lassen Ihnen gern ein individuelles Angebot zukommen.  
*More dimensions available upon request – we are happy to provide a detailed quotation.*

